

# Technical Datasheet

## AQUA BASE UNDERCOAT

**JUNO**

Product Code: 82414 Varnish &amp; Wood Treatments/ Varnish undercoat

### DESCRIPTION

**Odourless water-based clear and pore sealing preservative/undercoat for interior wood. Formulated with acrylic resins.**

### USE: INTERIOR

Recommended as a sandable undercoat for all kinds of joinery including doors, windows and frames, parquet and other wood surfaces.

Good filling power, easy application, and quick drying.

For use on both water-based and synthetic topcoats.

### PROPERTIES

- Good filling and sealing capacity
- Adjusts absorption of successive layers
- Provides a uniform finish
- Easy to sand down between application of each coat.
- Easy application
- Quick-drying
- Odourless

**Finish** Matt**Colour:** Colourless - Clear**Viscosity:** Min. 45" S/FR1002**Density:** 1,03 ± 0,05 gr/cc S/FR1001**Drying:** Touch dry in 30 minutes**Min. repaint time:** 4-6 hours**Thinner** Water**Practical coverage:** 8-10 m<sup>2</sup>/L (per coat)**flash point:** Not flammable**VOC Content:** Maximum 100 gr/ltr.

82414 INCOLORO



Format: 0,750 L / 4 L

The information contained in this data sheet may change and must be updated. Consult [www.junopaints.com](http://www.junopaints.com) or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.

Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio (SPAIN) • Tel.: +34 944 670 062 • [infoweb@juno.es](mailto:infoweb@juno.es) • [www.junopaints.com](http://www.junopaints.com)

# Technical Datasheet

## AQUA BASE UNDERCOAT



Product Code: 82414 Varnish & Wood Treatments/ Varnish undercoat

### PREPARACIÓN DE SUPERFICIES

**UNTREATED TIMBER.** The wood must be free of grease, sanded, clean and completely dry. Its moisture content should not exceed 15%. It is recommended to pretreat the wood with an insecticidal/fungicidal treatment if necessary. Very resinous woods must be previously cleaned with **D-45 thinner (Prod. Code 50.017)** to avoid drying problems. Subsequently, apply in thin and well-stretched coats, making sure to avoid sags and overlays. For better application result, product can be diluted with 10% water. Sand after at least three hours with 150 -180 grit sand paper.

### APPLICATION TIPS

Stir product well until complete homogenization. Apply on consistent, clean and completely dry surfaces. Dilute the product depending on the porosity and condition of the substrate. Apply the product with sufficient ventilation.

**ENVIRONMENTAL CONDITIONS.** Do not apply on surfaces with temperature of less than 5°C, nor on excessively warm substrates. Relative humidity should not exceed 80%. Do not apply when risk of rain or strong wind is present.

**APPLICATION METHOD.** Brush or roller. On very porous surfaces it is recommended to apply several coats.

**CLEANING.** Wash tools with water immediately after use.

### OBSERVATIONS

On lighter wood types, especially oak and chestnut, the product must be applied in thin coats - stretching coats well, to avoiding sagging and high thicknesses per coat as darkening of the wood can occur in high-build coating areas.

### SAFETY & ENVIRONMENT

Minimize the waste of the product estimating the real quantity needed, taking into account the m<sup>2</sup>, the porosity and texture of the substrate to be coated. Store leftover material in a ventilated and dry place. The container must be clean and of a suitable size for the quantity of excess product. Close the containers carefully and keep them upright to avoid spills. Preserve containers away from frost, high temperatures and direct sun exposure. Reuse leftover products to save the environment. Do not eat, drink or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding PPE and safety measures. For more information consult the Safety Data Sheet. In case of contact with eyes, wash with clean and abundant water. Keep out of the reach of children. Do not discharge into drains or the environment. Dispose of product at an authorized waste collection point. Consult your council about the correct recycling of both the packaging and waste and leftover paint according to law and principles of environmental respect.

The information contained in this data sheet may change and must be updated. Consult [www.junopaints.com](http://www.junopaints.com) or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.

Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio (SPAIN) • Tel.: +34 944 670 062 • [infoweb@juno.es](mailto:infoweb@juno.es) • [www.junopaints.com](http://www.junopaints.com)