

# JUNO

Juno Paints  
Industrias JUNO S.A.  
B.º Saconi, 10  
48950 ERANDIO (Vizcaya)  
Apdo. 461, 48080-BILBAO  
Tel.: +34 944 670 062  
Fax: +34 944 675 832  
export@juno.es

[www.junopaints.com](http://www.junopaints.com)



JPV1 10 XX17

# Floor coatings

& vertical coatings for industrial, healthcare, sports and logistical/traffic applications.



# JUNO



# Floor and vertical surface coatings

## Surface Preparation

### All surface types:

- Surfaces must be firm, dry, clean and porous, preferably floated and not polished.
- The surface humidity level cannot exceed 4% measured at 2 cm depth.
- Repair cracks, fissures and imperfections with suitable products.
- Once treated, remove dust efficiently before proceeding with application.

Once the surface is prepared, it is important to use a suitable **primer** to obtain an optimal and long-lasting finish.

### Concrete Surfaces:

- A minimum of 30 days must elapse after the concrete setting, before the paint application.
- On very smooth surfaces, carry out a mechanical milling, shot-blasting, sanding, sand-blasting) in order to favour the proper penetration and adhesion of the product.

### Asphalt Surfaces:

- Use water-based products to avoid discoloration and bleeding problems (
- Treat grease, oil and road stains, etc. with suitable solvents and /or detergents, rinse with water and allow surface to completely dry out. Sandblast if necessary.

## Water-based options

## Solvent-based options

### DYNAPOK AGUA FLOOR PRIMER 2/C 07.160

Two-component water-based epoxy primer with excellent mechanical and chemical properties. Adhesion to mineral surfaces and old paints, forming a very hard film.

Recommended for sealing and consolidating concrete, asphalt and food industry surfaces as well as places with poor ventilation. Also suitable as a protective finishing varnish (gloss finish) on concrete surfaces.

Finish: Clear. Finish: Satin. Dilution: Water.



### IMPRIMAX 2/C PRIMER 48.725

Two-component solvent-based epoxy primer. Great mechanical and chemical resistance, with excellent adhesion on mineral substrates, old paints and little porous surfaces.

Recommended for use in industrial applications, warehouses, covered/indoor parking lots and heavy traffic areas. Excellent as adhesion promoter on concrete surfaces, tiles, stoneware etc.

Color: Clear. Finish: Semi-gloss. Dilution: Do not dilute



## Topcoats


## Topcoats

### JUNOSOL

**One-pack water-based** floor paint. Great hardness and resistance to abrasion, good penetration power, ease of application, good adhesion, hardness and flexibility. Recommended for painting sports facilities, storage rooms, parking lots and concrete or asphalt surfaces.

Finish: Semi-matt

Cleaning and thinning: Use water.



White 06.162



Light Grey 06.164



Cement Grey 06.163



Tennis Green 06.150



Tennis Red 06.160



Yellow 06.166

### DYNAMOL

One-component quick-drying chlorinated rubber paint. Great resistance in industrial environments, tackling acids and alkalis. Good mechanical resistance.

Recommended for painting and protecting general surfaces, ground and parking signposting, garages, sports facilities, etc. Not recommended on tar and / or bituminous surfaces.

Finish: Satin

Cleaning and thinning: Chlorinated rubber thinner (D-40).



Certifications: Fire Retardant to B-s1, Anti-slip resistant to Class 3



White (RAL 9010) 09.500



Black 09.501



Pearl Grey 09.533



Tennis Green 09.552



Tennis Red 09.568



Bright Red 09.553



Yellow 09.525

### DYNAPOK 2-PACK WATER-BASED EPOXY

Two-pack water-based epoxy enamel. Excellent adhesion on mineral substrates and on previously painted surfaces. Great mechanical and chemical resistance and low VOC content.

Recommended for general use in industrial applications, especially suitable in food industries hospital and healthcare installations, showerrooms, asphalt surfaces, places with poor ventilation, or when a completely water-based system is specified or required.

Finish: Satin

Cleaning and thinning: Use water.



Green 07.144



English Red 07.143



Grey 07.145

### PAVIMYC 2/C EPOXY COATING

Two-component solvent-based epoxy coating. Provides strong adhesion and touch resistant finish.

Excellent chemical resistance, increases surface hardness and resistance to abrasion. Seals, waterproofs and protects surfaces.

Recommended for concrete floors in indoor parking lots and garages, laboratories, chemical and pharmaceutical plants, refineries, mechanical workshops and in general on all types of industrial and logistical floors, both new and old. Not recommended for tar and / or bituminous surfaces.

Finish: Gloss

Cleaning and thinning: D-90 Solvent/Thinner.



Certifications: Fire Retardant to B-s1, Anti-slip resistant to Class 3



English Red 07.812



Green 07.814




Grey 07.807

Also available in **Clear Finish** - Product Code: **07.815**

### JUNOMATIC TINTING SYSTEM



White (P-BASE) 07.132



Deep (TR-BASE) 07.133



Certifications: Fire Retardant to B-s1, Anti-slip resistant to Class 3  
Non-toxicity certificate: Non migration of certain elements EN 71-3:2013+A2:2017  
German AgBB 2018, A+ Certified for clean interior environment.

### FOR ANTI-SLIP OPTION

#### ADD ANTI-SLIP MICROBEADS

Polypropylene microbeads suitable allowing for non-slip properties on wet surfaces.

07.250



Certifications: Class 3 Anti-slip rated